

SPIGOLO FLOOR

Studiocharlie

Floor, wall/ceiling and pendant lamps based on an extruded and tubular aluminium structure, connected with moulded ABS joints, with white or black painted finish. Thanks to the joints, enabling the profiles to house LED sources, one can rotate 360° in order to produce a directional direct or indirect lighting, screened by an opaline diffuser in polycarbonate. The floor version is designed as such to provide a virtual divider to ambiances, while the ceiling and wall versions allow the enlightenment of the ambience in a versatile and a comfortable way. LED sources are dimmable and with warm tone.



LED

LAMPING

Source	3xlinear LED
Total power	8+12+41W
Emission	triple, diffused
Switching	mono switch, dimmable
Tension	110/240V
Color temperature	3000K
Luminous flux	800lm+1200lm+4100lm
Typ cri	83
Energy class	A+
Ip class	20
Materials	aluminium + PC + ABS
Notes	orientable diffuser, dimmer on cable, cable length 4,5m
Net lamp weight	10 Kg

Codes

SPI LWW 23

SPI LNN 23

Structure

white

black

PACKAGE

Package 01 57x78x16 cm / Gross weight: 6.5 Kg

Package 02 18 x22x190 cm / Gross weight: 7 Kg

Certificazioni

