











- Rectangular luminaire for installation in the wall – recessed.
- Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content). Glass diffuser: sandblasted.
- Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.
- Protection rating: IP65
- In compliance with EN 60598-1 standards
- Class of insulation: I, LED module: I, III
- Installation: wiring through two M16 plastic cable glands (4,5\times10mm) placed on the back side of the fitting. Outdoor use requires suitable flexible cables assuring the watertightness of the cable gland. Installation requires a dedicated box to be ordered separately.

EU Regulation 874/2012 - Illumination equipment energy classes

	LED VERSION: Class A/A+/A++ Luminaire supplied with integrated LED modules that cannot be replaced
	
	
	FLUORESCENT VERSION: Class A TC-DEL/G24q-2
	
	FLUORESCENT VERSION: Class A/B TC-D/G24d-3
	
	HALOGEN VERSION: Class D QT32/E27



Recessed wall fitting.



The fitting is equipped with 2 cable input.




Remote device required.





Protection against impact.
IK 08 - 5,00 joule



Alice / All Light





820123
 QT 32 60W E27





825923
 TC-DEL 18W G24q-2
 Electronic ballast



820923
 TC-D 26W G24d-3




Alice Power LED / All Light







8202001
 NATURAL WHITE 4000K
 MID-POWER LEDs
 8,8W/220÷240V
 Total power 11W
 lm LED 1258 ≈ lm OUTPUT 420
 CRI >80
 Integral electronic power supply

8202002
 WARM WHITE 3000K
 MID-POWER LEDs
 8,8W/220÷240V
 Total power 11W
 lm LED 1198 ≈ lm OUTPUT 400
 CRI >80
 Integral electronic power supply



Alice / Louvre







820105  
QT 32 60W E27




825905  
TC-DEL 18W G24q-2
Electronic ballast





820905  
TC-D 26W G24d-3





Alice / Horizontal Frame







820117  
QT 32 60W E27




825917  
TC-DEL 18W G24q-2
Electronic ballast



820917  
TC-D 26W G24d-3





Alice Power LED / Horizontal Frame





8220917

NATURAL WHITE 4000K
POWER LEDs
5,5W/100÷240V
Total power 8W
lm LED 650 ≠ lm OUTPUT 153
CRI >80
Integral electronic power supply





8212517

WARM WHITE 3000K
POWER LEDs
5,5W/100÷240V
Total power 8W
lm LED 600 ≠ lm OUTPUT 141
CRI >80
Integral electronic power supply



8225817


NATURAL WHITE 4000K
POWER LEDs
5,5W/24Vdc
Total power 6,7W
lm LED 650 ≠ lm OUTPUT 153
CRI >80
Remote electronic power supply to be ordered



8225917



WARM WHITE 3000K
POWER LEDs
5,5W/24Vdc
Total power 6,7W
lm LED 600 ≠ lm OUTPUT 141
CRI >80
Remote electronic power supply to be ordered

Alice Power LED / Vertical Frame





8218218

NATURAL WHITE 4000K
POWER LEDs
3,3W/100÷240V
Total power 6W
lm LED 342 ≠ lm OUTPUT 81
CRI >80
Integral electronic power supply





8212218

WARM WHITE 3000K
POWER LEDs
3,3W/100÷240V
Total power 6W
lm LED 321 ≠ lm OUTPUT 73
CRI >80
Integral electronic power supply



8226118

NATURAL WHITE 4000K
POWER LEDs
3,3W/24Vdc
Total power 4,5W
lm LED 342 ≠ lm OUTPUT 81
CRI >80
Remote electronic power supply to be ordered




8226218


WARM WHITE 3000K
POWER LEDs
3,3W/24Vdc
Total power 4,5W
lm LED 321 ≠ lm OUTPUT 73
CRI >80
Remote electronic power supply to be ordered

Accessories: Alice


77
BOX FOR INSTALLATION
236 x 136 H 110mm




150
POWER SUPPLY DUAL FUNCTION
Vout 24Vdc: 8W/100÷240V
Iout 350mA: 6x1W/100÷240V
IP20 CLASS II SELV EQ.




106
POWER SUPPLY DUAL FUNCTION
Vout 24Vdc: 8W/100÷240V
Iout 350mA: 6x1W/100÷240V
IP65 CLASS II SELV EQ.




87
POWER SUPPLY 10W/110÷240V -
24Vdc IP20 CLASS II SELV.




175
POWER SUPPLY 10W/110÷240V - 24Vdc
IP67 CLASS II SELV.




155
POWER SUPPLY 50W/120÷240V - 24Vdc
IP67 CLASS II SELV.



110
POWER SUPPLY 70W/220÷240V - 24Vdc
IP67 CLASS II SELV EQ.



237
SPD: (SURGE PROTECTION DEVICE) 275V_{ac}
MAXIMUM DISCHARGE CURRENT 10kA (8/20µs)
MAXIMUM OPERATING CURRENT 5A
SUITABLE FOR SERIES CONNECTION - IP66



acc. code ▶	77	150	106	87	175	155	110	237
prod. code ▼								
820105	•							
820117	•							
820123	•							
820905	•							
820917	•							
820923	•							
825905	•							
825917	•							
825923	•							
8202001	•							•
8202002	•							•
8212218	•							•
8212517	•							•
8218218	•							•
8220917	•							•
8225817	•			1	1	4	8	
8225917	•			1	1	4	8	
8226118	•	1	1	2	2	7	14	
8226218	•	1	1	2	2	7	14	

Max fixtures for each power supply (Vin 220÷240).
Data in the chart are provided as a guide only.
Please verify according to your installation.