












- Luminaire for installation on wall – surface mounted.
- Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content). Glass diffuser: sandblasted.
- Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders that are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components that have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.
- Protection rating: IP65.
- In compliance with EN 60598-1 standards.
- Class of insulation: I.
- Installation: wiring through M16 plastic cable gland (4,5mm\times10mm cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable gland.

EU Regulation 874/2012 - Illumination equipment energy classes

	LED VERSION: Class A/A+/A++ Luminaire supplied with integrated LED modules that cannot be replaced
	
	
	METAL HALIDE VERSION: Class A+ HIT-DE/RX7s
	FLUORESCENT VERSION: Class A TC-DEL/G24q-2
	
	FLUORESCENT VERSION: Class A/B TC-D/G24d-3
	
	HALOGEN VERSION: Class D QT32/E27



Wall fitting



The fitting is equipped with 1 cable input






Protection against impact.
IK 07 - 2,00 joule



Memi / Sandblasted Glass





490100 D
QT 32 100W E27





496000 A
TC-DEL 2x18W G24 q-2
Electronic ballast



491600 B A
TC-D 2x26W G24 d-3






492900 A*
HIT-DE 70W Rx7s
Electronic ballast



Memi Mid-Power LED / Sandblasted Glass



492700 A A* A**
NATURAL WHITE 4000K
MID-POWER LEDs
15W/220÷240V
Total power 18W
Lm LED 2422 ≠ Lm OUTPUT 1150
CRI>80
Integral electronic power supply




4927800 A A* A**
WARM WHITE 3000K
MID-POWER LEDs
15W/220÷240V
Total power 18W
Lm LED 2307 ≠ Lm OUTPUT 1095
CRI>80
Integral electronic power supply



Accessories: Memi

237
 SPD: (SURGE PROTECTION DEVICE) 275Vac
 MAXIMUM DISCHARGE CURRENT 10kA (8/20µs)
 MAXIMUM OPERATING CURRENT 5A
 SUITABLE FOR SERIES CONNECTION - IP66



acc. code	▶	237
prod. code	▼	
490100		
491600		
492900		
496000		
4927700		●
4927800		●