



- Slim rectangular or round luminaire for installation on wall – surface or recessed.
- Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content). Moulded transparent polycarbonate emitting unit (rectangular) or transparent polyurethane resin filling (round) and polished aluminium reflector fixed by double-sided technical tape.
- Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.
- Protection rating: IP65
- In compliance with EN 60598-1 standards
- Class of insulation: III
- Installation: the luminaire is equipped with a piece of cable for an easy-to-make connection. 24V feeding: power supply installed in a remote position; 230V feeding: power supply located behind the luminaire into the recessed box for installation (to be ordered separately). Outdoor use requires suitable flexible cables.
- We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

EU Regulation 874/2012 - Illumination equipment energy classes

**A++**  
**A+**  
**A**

**LED VERSION:**  
Class A/A+/A++  
Luminaire supplied with integrated LED modules that cannot be replaced




Recessed wall fitting.      Wall fitting




Pre-wired with approx 250mm of cable.      Remote device required.

Protection against impact. IK 08 - 5,00 joule

**Trixie Round Low-Power LED / Transparent Diffuser**




**526002** **A A+ A++**  
 NATURAL WHITE 4000K  
 LOW-POWER LEDs  
 1,5W/24Vdc  
 Total power 1,9W  
 lm LED 156 ≠ lm OUTPUT 74  
 CRI >80  
 Remote electronic power supply  
 to be ordered  
 Acc. 144 or 176






**526003** **A A+ A++**  
 WARM WHITE 3000K  
 LOW-POWER LEDs  
 1,5W/24Vdc  
 Total power 1,9W  
 lm LED 149 ≠ lm OUTPUT 71  
 CRI >80  
 Remote electronic power supply  
 to be ordered  
 Acc. 144 or 176

**Trixie Low-Power LED / Transparent Diffuser**



**10222900** **A A+ A++**  
 NATURAL WHITE 4000K  
 LOW-POWER LEDs  
 1,5W/24Vdc  
 Total power 1,9W  
 lm LED 156 ≠ lm OUTPUT 64  
 CRI >80  
 Remote electronic power supply  
 to be ordered  
 Acc. 144 or 176




**1029500** **A A+ A++**  
 WARM WHITE 3000K  
 LOW-POWER LEDs  
 1,5W/24Vdc  
 Total power 1,9W  
 lm LED 149 ≠ lm OUTPUT 61  
 CRI >80  
 Remote electronic power supply  
 to be ordered  
 Acc. 144 or 176




## Accessories: Trixie


**105**  
3 MODULES RECESSED BOX  
106 x 75 H 55mm




**150**  
POWER SUPPLY DUAL FUNCTION  
Vout 24Vdc: 8W/100÷240V  
Iout 350mA: 6x1W/100÷240V  
IP20 CLASS II SELV EQ.




**106**  
POWER SUPPLY DUAL FUNCTION  
Vout 24Vdc: 8W/100÷240V  
Iout 350mA: 6x1W/100÷240V  
IP65 CLASS II SELV EQ.




**87**  
POWER SUPPLY 10W/110÷240V -  
24Vdc IP20 CLASS II SELV.




**175**  
POWER SUPPLY 10W/110÷240V - 24Vdc  
IP67 CLASS II SELV.




**144**  
POWER SUPPLY 17W/110÷240V - 24Vdc  
(15W@110V) IP20 CLASS II SELV.



**176**  
POWER SUPPLY 17W/110÷240V - 24Vdc  
(15W@110V) IP67 CLASS II SELV.




**147**  
POWER SUPPLY 20W/220÷240V - 24Vdc  
IP67 CLASS II SELV.




... DIMMABLE: PUSH-DIM OR 1...10V  
See Page 514 Wiring Diagram n.4

... DIMMABLE: PUSH-DIM OR 1...10V  
See Page 514 Wiring Diagram n.4


**155**  
POWER SUPPLY 50W/120÷240V - 24Vdc  
IP67 CLASS II SELV.




**110**  
POWER SUPPLY 70W/220÷240V - 24Vdc  
IP67 CLASS II SELV EQ.




**156**  
POWER SUPPLY 96W/120÷277V - 24Vdc  
IP67 CLASS II SELV.



Trixie with box cod.105



Trixie without box cod.105



acc. code ▶	105	150	106	87	175	144	176	147	155	110	156
prod. code ▼											
526002	●	3	3	5	5	8	8	9	25	30	45
526003	●	3	3	5	5	8	8	9	25	30	45
1029500	●	3	3	5	5	8	8	9	25	30	45
10222900	●	3	3	5	5	8	8	9	25	30	45

Max fixtures for each power supply (Vin 220÷240). Data in the chart are provided as a guide only. Please verify according to your installation.